



COMSAN® PULSE DRAIN DISCHARGE CR BATTERY © Feb, 2018.



COMSAN®CR2032H

Rated Voltage: 3.0V

End Voltage: 2.0V

Operating Temp: -30°C to 85°C

Self Discharge: ≤2% / year

Pulse Drain Discharge(Cyclic&Continuous):

20mAh 20ms on / 20ms off to 2.0 volts

Capacity: 145mAh

Normal Continuous Discharge:

15kΩ/0.19mAh to 2.0 volts

Capacity: 240mAh

Normal Discharge Time: 1263Hours



COMSAN®CR2025H

Rated Voltage: 3.0V

End Voltage: 2.0V

Operating Temp: -30°C to 85°C

Self Discharge: ≤2% / year

Pulse Drain Discharge(Cyclic&Continuous):

20mAh 20ms on / 20ms off to 2.0 volts

Capacity: 116mAh

Normal Continuous Discharge:

15kΩ/0.19mAh to 2.0 volts

Capacity: 170mAh

Normal Discharge Time: 894Hours



COMSAN®CR1632H

Rated Voltage: 3.0V

End Voltage: 2.0V

Operating Temp: -30°C to 85°C

Self Discharge: ≤2% / year

Pulse Drain Discharge(Cyclic&Continuous):

20mAh 20ms on / 20ms off to 2.0 volts

Capacity: 65mAh

Normal Continuous Discharge(Continuous):

15kΩ/0.19mAh to 2.0 volts

Capacity: 140mAh

Normal Discharge Time: 736Hours



COMSAN®CR3032H

Rated Voltage: 3.0V

End Voltage: 2.0V

Operating Temp: -30°C to 80°C

Self Discharge: ≤2% / year

Pulse Drain Discharge(Cyclic&Continuous):

20mAh 20ms on / 20ms off to 2.0 volts

Capacity: 217mAh

Normal Continuous Discharge:

7.5kΩ/0.4mAh to 2.0 volts

Capacity: 600mAh (Continuous)

Normal Discharge Time: 1500Hours